

Photo report

Creation of a link road (testing area) in Salvador de Bahia by using NovoCrete®

- Location: Salvador de Bahia/Brazil
- Period of execution: August 2010
- Time needed: 1 day
- Cement: 200 kg/m³ + 2 % NovoCrete
- Milling depth: 30 cm

**AUTARK Energy & Infrastructure
Solutions GmbH & Co. KG**

Brienner Str. 9, D-80333 München, Germany

Phone +49 (0) 89-290 97 286

Fax +49 (0) 89-290 97 446

www.autark-energy.com

moormann@autark-energy.com

Soil stabilisation with NovoCrete®



Photo report: Creation of a link road in Salvador de Bahia

page 2



Delivery of the cement



Manually distribution of the cement

Photo report: Creation of a link road in Salvador de Bahia

page 3



Filling of the spreading unit with the cement additive NovoCrete®



Tractor with the attached spreading unit for the cement additive NovoCrete®

Photo report: Creation of a link road in Salvador de Bahia

page 4



Milling of the binding agent up to a milling depth of 0,30 m

Photo report: Creation of a link road in Salvador de Bahia

page 5



Use of a Grader for the levelling



Photo report: Creation of a link road in Salvador de Bahia



Static and dynamic compaction



Area after compaction

Photo report: Creation of a link road in Salvador de Bahia

page 7



Area (without asphalt layer) 4 months after finishing

Photo report: Creation of a link road in Salvador de Bahia

page 8



Area (without asphalt layer) 14 months after finishing

Photo report: Creation of a link road in Salvador de Bahia

page 9



Area (without asphalt layer) 14 months after finishing